Package: ordinalMIC (via r-universe)

October 22, 2026

Type Package

Title Minimum Inhibitory Concentration Estimation from Ordinal Regression Models

Version 1.0.0

Description Provides tools to estimate minimum inhibitory concentration (MIC) and conduct rigorous pairwise comparisons (delta, fold-change, and difference of difference tests) from cumulative-link models fitted with 'ordinal::clm'.

Depends R (>= 4.1)

Imports ggplot2, stats, utils, cli, tibble

Suggests ordinal, testthat (>= 3.0.0)

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Config/testthat/edition 3

URL https://clstacy.github.io/ordinalMIC/

Repository https://clstacy.r-universe.dev

Date/Publication 2025-09-15 18:26:31 UTC

RemoteUrl https://github.com/clstacy/ordinalMIC

RemoteRef HEAD

RemoteSha 6cfa30981e164c82a1baf6146343ec48e0669e1f

Contents

autoplot.mic_solve 2
mic_solve 3
tidy.mic_solve 4
yeast_df 5

Index **6**

`autoplot.mic_solve` *autoplot method for mic_solve objects*

Description

Quick ggplot2 visualisations of the main outputs from `mic_solve()`. Three panels are supported:

- **"mic"** - forest plot of group-wise MIC estimates with asymmetric CIs.
- **"delta"** - forest plot of deltaMIC pairwise differences.
- **"ratio"** - forest plot of MIC ratios (log scale).

Usage

```
## S3 method for class 'mic_solve'
autoplot(
  object,
  type = c("mic", "delta", "ratio", "DoD_delta", "DoD_ratio"),
  x = NULL,
  color_by = NULL,
  dot_size = 0.5,
  ...
)
```

Arguments

`object`	An object returned by `mic_solve()`.
`type`	One of `"mic"`, `"delta"`, or `"ratio"`, `"DoD_delta"`, or `"DoD_ratio"`.
`x`	Variable for x axis plotting
`color_by`	Optional column name used to color and dodge replicate points. Default: first column in `newdata`.
`dot_size`	Size of the dots in the dotplot. Default: `0.5`.
`...`	Additional arguments passed to `ggplot2::ggplot()`.

Value

A **ggplot** object.

Author(s)

Carson Stacy

Examples

```
if (requireNamespace("ordinal", quietly = TRUE) &&
    requireNamespace("ggplot2", quietly = TRUE)) {
  df <- data.frame(score  = ordered(sample(0:4, 120, TRUE)),
                   conc   = runif(120, 0, 4),
                   strain = factor(sample(c("A","B"), 120, TRUE)))
  fit <- ordinal::clm(score ~ strain * log1p(conc), data = df)
  res <- mic_solve(fit, expand.grid(strain = levels(df$strain)),
                   conc_name = "conc")
  ggplot2::autoplot(res, type = "mic")
}
```

`mic_solve` *Estimate MICs and Compare Groups*

Description

High-level wrapper that returns:

- `delta_mic_results` – additive pairwise differences (Δ-MIC).
- `ratio_mic_results` – multiplicative pairwise ratios.
- `dod_ratio_results` – **difference-of-differences on the ratio scale** (ratio-of-ratios, a classic interaction on the log scale).
- `dod_delta_results` – **difference-of-differences on the additive scale** (Δ of Δs).

Usage

```
mic_solve(
  clm_fit,
  newdata = NULL,
  conc_name,
  transform_fun = log1p,
  inv_transform_fun = expm1,
  alpha = 0.05,
  compare_pairs = "all",
  pvalue_scale = c("lp", "logmic")
)
```

Arguments

`clm_fit`	Fitted object from `ordinal::clm()`.
`newdata`	Data frame with factor combinations to evaluate.
`conc_name`	Character string giving the **raw** concentration column.
`transform_fun`	Transformation used in the model (default `log1p`).

`inv_transform_fun`
: Inverse transformation (default `expm1`).

`alpha`
: Confidence-level significance (default 0.05).

`compare_pairs`
: One of `"all"` (default) to retain every pairwise comparison, or `"share_any"` to exclude contrasts where the two groups share no covariate levels in `newdata`.

`pvalue_scale`
: Which pivot the main P_value uses for pairwise tests: ”lp” (difference in lp = log1p(MIC), recommended for calibration) or ”logmic” (current Wald on log(MIC) for ratios and MIC scale for deltas).

Value

An object of class `"mic_solve"` containing the tables above plus `mic_estimates`.

Examples

```
if (requireNamespace("ordinal", quietly = TRUE)) {
  ## Toy ordinal dataset
  set.seed(1)
  fit <- ordinal::clm(score ~ strain * treatment + log1p(conc), data = yeast_df)
  res <- mic_solve(fit, conc_name = "conc")
  head(res$ratio_mic_results)
}
```

---

tidy.mic_solve *tidy method for mic_solve objects*

Description

tidy method for mic_solve objects

Usage

```
tidy.mic_solve(
  x,
  table = c("mic", "delta", "ratio", "DoD_delta", "DoD_ratio"),
  ...
)
```

Arguments

`x`
: An object of class `mic_solve`.

`table`
: A character string specifying which table to return. Options are `"mic"`, `"delta"`, `"ratio"`, `"DoD_delta"`, and `"DoD_ratio"`.

`...`
: Additional arguments (not used).

Value

A tibble containing the requested table from the `mic_solve` object.

`yeast_df` *Simulated Yeast Stress-Survival Data*

Description

An example dataset with ordinal spot scores (0 = no growth … 4 = full growth) for treated and untreated wild-type and mutant yeast across a peroxide gradient.

Usage

```
data(yeast_df)
```

Format

A data frame with 132 rows and 4 variables:

score Ordered factor `0 < 1 < 2 < 3 < 4`

conc Numeric concentration units

strain Factor: `"WT"` or `"Mut"`

treatment Factor: `"None"` or `"Salt"`

rep Replicate id (integer)

Examples

```
data(yeast_df)
head(yeast_df)
```

Index

∗ **datasets**
yeast_df, 5

autoplot.mic_solve, 2

ggplot2::ggplot(), *2*

mic_solve, 3
mic_solve(), *2*

ordinal::clm(), *3*

plot.mic_solve *(autoplot.mic_solve)*, 2

tidy.mic_solve, 4

yeast_df, 5